

Product Description		
Construction (絨面結構)	Textured Patterned Loop	高低圖案圈毛
Pile Fiber (絨毛成分)	100% J&J Encore® SD Ultima® Nylon	100% J&J Encore® SD Ultima® 尼龍
Dye Method (染色方式)	Solution	原液染色
Gauge (針距)	1/12 (4.72 rows / cm)	1/12 吋
Pile Weight (絨毛重量)	21 oz/sq yd (712 g/m ²)	21 盎司/平方碼 (712克/平方米)
Pile Density (絨毛密度)	7,370 oz/y3 (273.3 kg/m ³)	7,370盎司/立方碼 (273.3公斤/立方米)
Pile Height (絨毛高度)	3mm	3mm
Primary Substrate (第一層基層)	100% Synthetic	100% 合成
Backing Structure (底層結構)	eKo® Modular	eKo® 底
	ProTex® (Soil Release)	ProTex® (Soil Release)
Special Technology (特殊技術處理)	Stain/Bleach Resistant	Stain/Bleach Resistant
	Sentir™ Odor Blocking	Sentir™ Odor Blocking
Tile Size (單片尺寸)	24" x 24" (61 cm x 61 cm)	24英吋x 24英吋 (61 公分 x 61 公分)
Packing (包裝)	18 pcs per carton	18 片/箱



This product has been passed in its quality and anti-combustion by the carpet supervision test center (Foundation fire retardant safety center) of the states and the anti-fire department of the states.
 此產品通過國家財團法人消防安全中心基金會的質量標準測試，符合國家消防部門阻燃性檢測標準

PERFORMANCE TESTS - International standard

Characteristics	Method	Typical values	Results
Sustainable Carpet Assessment Standard (地毯耐用性評估標準)	NSF 140	Gold	Gold
Indoor Air Quality (室內空氣品質)	CRI Green Label Plus	GLP 9716	PASS (合格)
Total Recycled Content (可循環使用百分比)		14%-19%	
Methenamine pill test (六亞甲基四胺測試)	ASTM-D-2859	PASS (合格)	PASS (合格)
Flooring radiant panel test (輻射通量測試)	ASTM-E-648	Class 1	PASS (合格)
N.B.S. smoke chamber test (煙霧室測試)	ASTM-E-662	< 450 (Flaming Mode)	PASS (合格)
Electrostatic propensity test (抗靜電測試)	AATCC-134	< 3 kv	PASS (合格)
Lightfastness (耐光性測試)	AATCC-16E	PASS (合格)	PASS (合格)