## Construction (毯面結構) Textured Patterned Loop 高低圖案圈毛 Pile Fiber (絨毛成分) 100% Antron Lumena Type 6.6 Nylon 100% Antron Lumena 尼龍 6.6 Dye Method (染色方式) Solution 原液染色 Gauge (針距) 1/10 (39.37 per 10 cm) 1/10 时 Pile Weight (絨毛重量) 17 oz/sq yd (576 g/m<sup>2</sup>) 17 盎司/平方碼 (576 克/平方米) Pile Height (絨毛高度) 0.123" (3.12mm) 0.123英吋 (3.12公厘) Primary Substrate (第一層基層) 100% 合成 100% Synthetic Backing Structure (底層結構) Infinity Infinity Tile Size (單片尺寸) 24" x 24" (60.96 cm x 60.96 cm) 24英吋x 24英吋 (60.96 公分 x 60.96 公分)

## Packing (包裝) 14 pcs per carton in its quality and anti-combustion by the carnet supervision test center (Foundation fire retardant safety center) of the states and the anti-fire department of the states

**Product Description** 

Characteristics

Methenamine pill test (六亞甲基四胺測試)

Flooring radiant panel test (輻射通量測試)

N.B.S. smoke chamber test (煙霧室測試)

Electrostatic propensity test (抗靜電測試)

防焰	此產品通過國家財團法人防焰安全中心基金會的質量標準測試,符合國家消防部門阻燃性檢測標準
PERFORMANCE TESTS - International standard	

Method

ASTM-D-2859

ASTM-E-648

ASTM-E-662

AATCC 134

14 片/箱

Typical values

Class I (Direct Glue)

< 450 (Flaming Mode)

Passes

< 3.0 KV

Results

PASS (合格)

PASS (合格)

PASS (合格)

PASS (合格)