

Product Description		
Construction (毯面結構)	Multi-level Loop	多層次圈毛
Pile Fiber (絨毛成分)	50%Nylon+50% BCF Polypropylene	50%尼龍 50%BCF PP合成纖維
Dye Method (染色方式)	Solution dyed	原液染色
Gauge (針距)	1/12 INCH	每一英寸12針
Pile Weight (絨毛重量)	20.1oz./sq.yd.(570g/Sq.m.) +/- 5%	每平方米570g+/-5%
Average Pile Height (絨毛高度)	4.0 +/- 0.5mm	4.0+/-0.5毫米
Total Thickness (成品厚度)	6.5 +/- 0.5mm	6.5+/-0.5毫米
Primary Backing (第一層基布)	Polyester spunbonded	聚脂無紡不織布
Backing Structure (底層結構)	Glass reinforced PVC	聚氯乙炔內加玻璃纖維
Tile Size (單片尺寸)	50cm x 50cm	50公分*50公分
Packing (包裝)	20 pcs per carton(5m ²)	20片/箱(5平方米)



This product has been passed in its quality and anti-combustion by the carpet supervision test center (Foundation fire retardant safety center) of the states and the anti-fire department of the states.
 此產品通過國家財團法人防焰安全中心基金會的質量標準測試，符合國家消防部門阻燃性檢測標準

PERFORMANCE TESTS - EU standard

Wear Classification (耐用性)	Heavy Contract
Dimensional Stability (尺寸穩定性)	< +/-0.1%
Color Fastness to Light (耐光色牢度)	ISO105-B02 Grade 5 or higher
Color Fastness to Rubbing (耐磨色牢度)	EN ISO 105-X12 Grade 4 or higher
Static Electrical Resistance (抗靜電性)	Stage II (U30=0.7)
Environmental Testing (環保性能)	Stage A (TVOC=0.293mg/sq.m.h; Styrene=0.073mg/sq.m.h; No Formaldehyde; No 4-Phenylcyclohexene)